


Para telefonia e cabling (rede estruturada) / For telephony and cabling



Para conectores 6P6C, 6P4C e 6P2C

For 6P6C, 6P4C and 6P2C connectors


HT-2096



Para conectores 8P8C(RJ45)

For 8P8C connectors


MT-210C



Para plugs 6P (RJ11, 12) e 8P (RJ45)

For 6P (RJ11,12) and 8P (RJ 45) plugs


HY-376E



Para plugs 8P8C(RJ45), 6P6C(RJ12) e 6P4C(RJ11) (com catraca)

For 8P8C (RJ45), 6P6C (RJ12) and 6P4C (RJ11) plugs (with ratchet)

MT-568R



Para conectores 8P8C (RJ45), 6P6C (RJ12) e 6P4C (RJ11) (com catraca)

For 8P8C (RJ45) 6P6C (RJ12) and 6P4C (RJ11) (with ratchet)

MT-500R



Decapador para cabos UTP/STP

Stripper for UTP/STP cables

HT-501



Testador de continuidade/seqüência de cabos montados com RJ11, RJ12 e RJ45

Testa a correspondência de cabos par-trançado, e pode detectar conexões erradas, curto circuitos e circuitos abertos. Duas velocidades de leitura. Utiliza bateria de 9VCC, não inclusa.

Continuity tester/ sequence of cables with RJ11, RJ12 and RJ45. Tests the correspondence of cables and, can detect wrong connections, short-circuit and open circuit. 2 speed scan. 9 VDC battery, not included.

NS-468




Para uso com Keystone Jack, lâmina tipo Krone

Aplicável às caixas de superfície CSMJ-1 e CSMJ-2

For Keystone Jack, Krone blade type

For CSMJ-1 e CSMJ-2


HY-3141A



Punch down para Keystone Jack com lâmina tipo 110 (permite o ajuste de pressão)

Punch down for keystone Jack with 110 blade type (allows pressure adjustment)

MT-314B



Punch down para uso com Keystone Jack, lâmina tipo 110

Punch down to use with Keystone Jack, 110 blade type

HT-3340/14B

Decapadores de fios / Wire Strip



Decapador para fios com Ø de 0,5 a 6mm

Wire stripper for wires with diameter 0.5 to 6mm

HY-150B




Decapador Bitolas Ø: 0,5; 1,2; 1,6 e 2mm

Empunhadura verde

Cable stripper for cables with diameter of 0.5; 1.2; 1.6 and 2mm

Green handle

HY-369A




Decapador Bitolas Ø: 1; 1,6; 2; 2,6 e 3,2mm

Empunhadura vermelha

Cable stripper for cable with diameter of 1; 1.6; 2; 2.6 and 3.2mm.

Red handle

HY-369B



Decapador Bitolas AWG: 22; 18-20; 14-16; 12; 10 e 8

Empunhadura amarela

Cable stripper for cables AWG: 22; 18-20; 14-16; 12; 10 and 8mm.

Yellow handle

HY-369C

Alicates diversos para elétrica e eletrônica / Several cutters for electricians and electronics



De aço carbono, com corte paralelo (Eletrônica)

Cutter for electronics, parallel cut

MT-1091



De liga de aço para fios de cobre ou alumínio até 18AWG

Cutter for 18AWG aluminum or copper wires

HT-222



Alicate de ponta chata (lisa)

Comprimento: 5,2" (133mm)

Flat plier 5.2" length (133mm)

HY-21B



Alicate de ponta fina e longa

Comprimento: 6" (153mm)

Fine and long plier 6" length (153mm)

HY-21C




Alicate universal

Comprimento: 5" (125mm)

Universal plier 5" length (125mm)

HY-21K



Alicate de corte

Comprimento: 4,6" (118mm)

Cutting plier 4.6" length (118mm)

HY-21X



MICRO ALICATE de corte com revestimento do cabo de borracha

Micro cutter plier with rubber handle

HY-501A








MICRO ALICATE com ponta curva e revestimento do cabo de borracha

Micro flat nose plier with rubber handle



HY-501C

Pinças / Tweezers



Pinças inoxidáveis e anti-magnéticas. Stainless anti-magnetic tweezers.

 <p>TS-10 Padrão / Standart</p>	 <p>TS-11 Grande / Big</p>	 <p>TS-12 Robusta / Strong</p>	 <p>TS-13 Ponta chata / Round</p>	 <p>TS-14 Ponta extra-fina / Extra fine</p>	 <p>TS-15 Ponta curva / Angle</p>
---	--	--	---	---	---

Extrator de CI / CI extractor

 <p>Extrator de CIs tipo DIL IC DIL type extractor</p>	 <p>Extrator de CIs tipo PLCC IC PLCC type extractor</p>
HT-103A	HT-103B

DIP PLUG, IDC e cabo plano / DIP PLUG, and IDC flat cable

 <p>Para DIP PLUG 0,3"/0,6" com cabo plano For DIP PLUG 0,3"/0,6" connectors crimping on flat cable</p>	 <p>Para conectores IDC a cabo plano (flat cable) For IDC connectors crimping on flat cable</p>
HT-214D	HT-214

Para uso com cabos coaxiais e conectores tipo F, BNC e TNC / For use with coaxials and F, BNC and TNC connectors

 <p>Para conectores F Cabo RG59, 62 e 6 For F connectors Cables RG 59, 62 and 6</p>	 <p>Para conectores F Cabo RG59, 62 e 6 For F connectors Cables RG 59, 62 and 6</p>	 <p>Para conectores F Cabos RG58, 6, 11 e 213 For F connectors Cables RG58, 6, 11 and 213</p>
HT-102H	HT-106C	HT-106E

 <p>Para conectores de compressão tipo F, BNC e RCA com regulagem de distância de compressão Cabos RG59/RG6 For compression connectors, type F, BNC and RCA, with adjustable compression distance. For use with RG59/RG6 cables</p>	 <p>Para conectores de compressão tipo F, BNC e RCA com cabos RG59/RG6. Dois valores para a distância de compressão 19,3 ou 21,0mm For compression connectors type F, BNC and RCA with RG59-RG6 cables. Two values for compression distance 19,3mm or 21,0mm</p>
HY-5081R	HY-5085

 <p>Para conectores F Cabo RG59, 62 e 6 For F connectors Cables RG 59, 62 and 6</p>	 <p>Para conectores coaxiais. Cabos RG58, 59, 62 e 6 (com catraca) For coaxial connectors Cables RG58, 62 and 6 (with ratchet)</p>	 <p>Kit Coaxial Coaxial Kit HT-301A + HT-206 Cortador de cabo/ Cable cutter + HT-312B Decapador/ Cable stripper</p>
HT-106H	HT-336C	HT-3014

 <p>Para conectores coaxiais para cabos RG58, 59, 140, 210, Belden 8279, 141, 142, 223, 303, 400 e fibra ótica (possui catraca) For coaxial connectors to cables RG58, 59, 140, 210, Belden 8279, 141, 142, 223, 303, 400 and optical fibers (has ratchet)</p>	 <p>Decapador para cabos coaxiais RG58, 59, 62 e 6. Modelo com 2 lâminas Cable stripper for coaxial cables RG58, 59, 62 and 6 Model with 2 blades</p>
HT-301A	HT-332

Para uso com terminais elétricos (painéis e/ou placa-cabo) / For use with electricals terminals (panels and/or cable-board)



Para terminais de conectores cabo-placa: PCT2, PCT3, MLTF e VT5
For wire to board connectors terminals: PCT2, PCT3, MLTF and VT5

HT-225D



D-sub 26-28AWG, emendas isoladas 22-26AWG, terminais telefonia tipo "U" (spade lug) 22-26AWG, terminais não isolados tipo Faston ou olhal nas bitolas 20-22 AWG e 14-18AWG
D-sub 26-28AWG, insulated joiners 22-26AWG, telephone terminals "U" type (spade lug) 22-26AWG, non insulated terminals Faston type or ring type


HT-202A



Legendas / Subtitles:











- Corta / Cut
- Crimpa / Crimp
- ▲ Decapa / Strip
- ◆ Fixa / Fasten
- ✕ Extraí / Extract

Para uso com terminais elétricos (painéis e/ou cabo-placa) / For use with electricals terminals (panels and/or wire to board)



Para terminais isolados e não isolados. Cunhas adequadas para cada tipo de terminal (vendidas separadamente)
For insulated and non insulated terminals. Dies sets for each type of terminal are sold separately.

MT-336FM

Cunha (Die)		Bitolas de cabos aplicáveis / Applicable cable gauges	Terminais aplicáveis / Applicable terminals
Desenho / Drawing	Código / Model		
	2C	AWG 20~18 / 16~14 / 12~10 DIN 0,5~1 / 1,5~2,5 / 4~6mm ²	 Terminais não isolados de barras abertas / Non insulated terminals
	2E	AWG 22 / 20 / 18 / 16 / 14 / 12 DIN 0,5 / 0,75 / 1,0 / 1,5 / 2,5 / 4mm ²	 Terminais isolados tipo tubular / Insulated tubular terminals
	2E1	AWG 10 / 8 / 6 DIN 6 / 10 / 16 mm ²	 Terminais isolados tipo tubular / Insulated tubular terminals
	2H	AWG 22~18 / 16~14 / 12~10 DIN 0,5~1,0 / 1,5~2,5 / 4~6 mm ²	 Terminais isolados / Insulated terminals
	2W	AWG 22~18 / 16~14 / 12~10 DIN 0,5-1,0 / 1,5~2,5 / 4~6 mm ²	 Terminais isolados / Insulated terminals