


WIW1029(3296) Trimmer Potentiometer



Features

- 9mm Square Multiturn
- Cermet / Industrial / Sealed
- 5 Terminals types (W / X / P / Y / Z)
- Available with a knob for finger adjust

Electrical Characteristics



Standard Resistance Range
10 to 5 megohms
(see standard resistance table)
Resistance Tolerance
 $\pm 10\%$ std.
(tighter tolerance is available)
Absolute Minimum Resistance
1% or 2 ohms max.
(whichever is greater)
Contact Resistance Variation
3% or 3 ohms max.
(whichever is greater)
Adjustability
Voltage $\pm 0.01\%$
Resistance $\pm 0.05\%$
Resolution: Infinite
Insulation Resistance
500 Vdc
1,000 megohms min.
Dielectric Strength
101.3 kPa 600 Vac
8.5 kPa 360 Vac
Effective Travel: 25turns nom

Environmental Characteristics


Power Rating (300 volts max.)
0.5 watt (70°C), 0 watt (125°C)
Temperature Range
-55°C to +125°C
Temperature Coefficient
 $\pm 100\text{ppm}/^\circ\text{C}$
Vibration
98 m/s²
(1% Δ TR; 1% Δ VR)
Shock
390 m/s²
(1% Δ TR; 1% Δ VR)
Load Life
1,000 hours 0.5 watt @ 70°C
(3% Δ TR; 4% or 4 ohms, whichever
is greater, CRV)
Rotational Life: 200 cycles
(3% Δ TR; 4% or 4 ohms)

Physical Characteristics


Torque
36 mN • m max.
Mechanical Stops
Wiper idles
Terminals
Solderable pins
Standard Packaging
50pcs.per tube




WIW3296W




WIW3296X



WIW3296P



WIW3296Y



WIW3296Z


How to order

WIW3296 - W - 102

Model _____

Style _____

Resistance code _____



Standard Resistance Table

Resistance Ohms	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500, 000	504
1, 000, 000	105
2, 000, 000	205
5, 000, 000	505

Special resistance is available
TCR of shaded areas $\pm 250\text{ppm}/^\circ\text{C}$
Detail Specification: Q/R Y256-2000
Detail Mil-Spec: Q/R Y20021-2000