






Sensores de Proximidade Indutivos

DC 3 Fios
M8
S_n 1,5 mm

M8x1 Faceada 1,5 mm 0...1,2 mm	M8x1 Faceada 1,5 mm 0...1,2 mm	M8x1 Faceada 1,5 mm 0...1,2 mm	M8x1 Faceada 1,5 mm 0...1,2 mm	M8x1 Faceada 1,5 mm 0...1,2 mm
				
	BES 516-324-E0-C-... BES 516-377-E0-C-...	BES 516-146-E0-X-...	BES 516-324-E3-L-...	BES 516-324-E3-C-...
BES 516-343-F0-L-...	BES 516-343-E0-C-... BES 516-378-E0-C-...		BES 516-343-E3-L-...	
24 V DC 10...30 V DC ≤ 1,5 V 250 V AC 200 mA ≤ 25 mA/≤ 12 mA ≤ 80 µA sim não -	24 V DC 10...30 V DC ≤ 1,5 V 250 V AC 200 mA ≤ 8 mA/≤ 1 mA ≤ 10 µA sim sim ≤ 0,5 µF	24 V DC 10...30 V DC ≤ 1,5 V 75 V DC 200 mA ≤ 25 mA/≤ 20 mA ≤ 80 µA sim não ≤ 1,0 µF	24 V DC 10...30 V DC ≤ 1,5 V 75 V DC 200 mA ≤ 25 mA/≤ 12 mA ≤ 80 µA sim não ≤ 1,0 µF	24 V DC 10...30 V DC ≤ 2,5 V 250 V DC 200 mA ≤ 9 mA/≤ 3 mA ≤ 20 µA sim sim ≤ 0,5 µF
≤ 5 % -25...+70 °C 1000 Hz DC 13 sim	≤ 5 % -25...+70 °C 3000 Hz DC 13 sim	≤ 5 % -25...+70 °C 1000 Hz DC 13 sim	-25...+70 °C 1500 Hz DC 13 sim	≤ 5 % -25...+70 °C 3000 Hz DC 13 sim
IP 67 II □ latão niquelado PBTP cabo 3 × 0,14 mm²	IP 67 latão niquelado PBTP cabo 3 × 0,14 mm²	IP 67 latão niquelado PBTP cabo 4 × 0,14 mm²	IP 67 latão niquelado PBTP cabo 3 × 0,14 mm²	IP 68 conf. BWN Pr. 20 II □ latão niquelado PA 12 cabo 3 × 0,14 mm²



6

Para conectores e suportes, ver pág. 6.2 ...