

## Datasheet

Art.No. 70.350.2435.1

Hood BAS GOT GA 24 M25 A1

revos BASIC size 24 hood with threaded collar M25, lateral cable entry, double locking lever



Art.No.	70.350.2435.1
EAN	4015573598713
Order unit	1 pieces

## Approvals



## Technical data

### General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Model

DIN-size	24
Model	male
Locking mechanism	Double locking levers
Cable entry	Sideways
Type of cable	Thread
With cable screw gland	No
Thread size M	25
Thread size PG	
Hinged lid	No
EMC-version	No
Length	120 mm
Width	57 mm
Height	70 mm

**Classification**

ECLASS 8.1	27440202
ETIM 6.0	EC000437
ETIM 5.0	EC000437
ETIM 4.0	EC000437
ETIM 3.0	EC000437



Drawings

Varianten/ Variants

70.350.3-2435.5	BAS 60T 6A 24 M25	M32 A5	Kabelverschraubung(KV), IP65 /cable gland(FG), IP65
70.350.4-2435.4	BAS 60T 6A 24 M25 A4	M32 A4	KV mit Zugentlastung, IP65 /KV with strain relief, IP65
70.350.3-2435.3	BAS 60T 6A 24 M25 A3	M32 A3	KV mit Zugentlastung und Keilschutz, IP65 /KV with strain relief and lock support, IP65
70.350.3-2435.2	BAS 60T 6A 24 M25 A2	M32 A2	Zwischenstützen /Bushing
70.350.3-2435.1	BAS 60T 6A 24 M25 A1	M32 A1	Gewindebohrung /Thread hole
70.350.3-2435.0	BAS 60T 6A 24 M25 A0	M32 A0	Kabelverschraubung(KV), IP65 /cable gland(FG), IP65
Bestellnummer /Order number		Typ /Type	Varianten /Variants

Bitte beachten: **Weitere Daten siehe KATALOG oder eKatalog.** [www.wieland-electric.com](http://www.wieland-electric.com)  
**Additional data see CATALOG or eCatalog.** [eshop.wieland-electric.com](http://eshop.wieland-electric.com)

Information: For 100% compatibility with other systems, the wiring terminals and dimensions are identical to the standard terminals. The dimensions of the terminals are given in millimeters unless otherwise specified. The dimensions of the terminals are given in millimeters unless otherwise specified. The dimensions of the terminals are given in millimeters unless otherwise specified.

Bestellnummer /Order number 70.350.3-2435.0	Typ /Type BAS 60T 6A 24 M25 A0	M32 A0	Kabelverschraubung(KV), IP65 /cable gland(FG), IP65
--	-----------------------------------	--------	--

**GEHÄUSEOBerteil**  
 Baugröße 24-Kabelabgang 5A(11)-16A(25)002  
 Housing size 24-cable out let 5A(11)-16A(25)002