

## Datasheet

Art.No. 70.353.3235.1

Hood BAS GOT GA 32 M40 50 A1

revos BASIC size 32 hood with threaded collar M40, lateral cable entry, double locking lever



Art.No.	70.353.3235.1
EAN	4015573629035
Order unit	1 pieces

## Approvals



## Technical data

### General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Model

DIN-size	32
Model	male
Locking mechanism	Double locking levers
Cable entry	Sideways
Type of cable	Thread
With cable screw gland	No
Thread size M	40
Thread size PG	
Hinged lid	No
EMC-version	No
Length	94 mm
Width	83 mm
Height	94 mm

**Classification**

ECLASS 8.1	27440202
ETIM 6.0	EC000437
ETIM 5.0	EC000437
ETIM 4.0	EC000437
ETIM 3.0	EC000437

Drawings

**Dimensions:** 37.5, 13.5, 91.5, 27, 18, 22, 101, 27, 91.5, 74, 91.5, 30

**Views:**

- Ausführung .1** (version .1): Gewinde M40 / thread M40
- Ausführung .2** (version .2): Stütze M40 / threaded support with thread M40
- Ausführung .3** (version .3): Kabelverschraubung M40 mit Japoptreling 107 / cable gland M40 with strain relief and line protection
- Ausführung .4** (version .4): Kabelverschraubung M40 mit Japoptreling 107
- Ausführung .5** (version .5): Kabelverschraubung M40 cable gland

**IP 65**

Teil-Nr.	Typ
70.353.3235.0	BAS GBT GA 32 M40 50 A0
70.353.3235.1	BAS GBT GA 32 M40 50 A1
70.353.3235.2	BAS GBT GA 32 M40 50 A2
70.353.3235.4	BAS GBT GA 32 M40 50 A4
70.353.3235.5	BAS GBT GA 32 M40 50 A5

**GEHAUSEOBerteil**  
Housing - Lateral cable entry

**Wieland**  
Industrie- und  
Vollstromsysteme

**70.353.3235.0 01K**

**Weitere Daten siehe Katalog**  
further data see catalog

**Ausführung .1**  
**Ausführung .2**