

## Datasheet

Art.No. 70.331.1635.1

Bottom BAS GUT GC 16 M25 A1

revos BASIC size 16 closed-bottom base with threaded collar M25, left double locking lever



Art.No.	70.331.1635.1
EAN	4015573599567
Order unit	1 pieces

## Approvals



## Technical data

### General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Model

DIN-size	16
Model	Surface mounting (base)
Locking mechanism	Double locking levers
Cable entry	Sideways
Type of cable	Thread
With cable screw gland	No
Thread size M	25
Thread size PG	
Hinged lid	No
EMC-version	No
Length	117 mm
Width	57 mm
Height	57 mm

**Classification**

ECLASS 8.1	27440202
ETIM 6.0	EC000437
ETIM 5.0	EC000437
ETIM 4.0	EC000437
ETIM 3.0	EC000437

Drawings

Varianten/Variants  
.0

**Bohrbild /Cut out**

70.331.1635.1	BAS GUT 6C 16 M25 A1	Gehäusebohrung /Thread hole	X
70.331.1635.0	BAS GUT 6C 16 M25 A0	Kabelverschraubung (KVV, PPS, montiert) /Cable gland (CGI, PPS, assembled)	
Buchsennummer /Order number	Typ /Type	Varianten /Variants	Anzahl /Quantity

**Weitere Daten siehe KATALOG oder eKatalog. Additional data see CATALOG or eCatalog.** [www.wieland-electric.com](http://www.wieland-electric.com)

Bohrung für 10 T10/TD/TD-Formate (siehe S. 10) (T10SD). Die Bohrung ist für die Montage von T10SD-Steckern vorgesehen. Die Bohrung ist für die Montage von T10SD-Steckern vorgesehen. Die Bohrung ist für die Montage von T10SD-Steckern vorgesehen. Die Bohrung ist für die Montage von T10SD-Steckern vorgesehen.

Z	Bestellnummer /Order number	T10SD	T10SD	T10SD	T10SD	T10SD	T10SD	T10SD	T10SD
	70.331.1635.1	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0
	70.331.1635.1	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0	70.331.1635.0

**GEHÄUSEUNTERTEIL**  
Bohrung für Kabelabgang in M25-Linse  
Housing size for cable outlet in M25-Linse