

Datasheet

Art.No. 96.062.4053.6

Connector RST20I6S S1 ZR1 TB04

RST 20I7/6 connector, 6 pole, male, screw connection, application 250V/400V, 20A, for cable diameters 6-10mm, coding color turquoise blue, color of housing black



Art.No.	96.062.4053.6
EAN	4049088423581
Order unit	1 pieces

Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	L, N, PE, 1, 2, Ls
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter max.	10 mm
Cable diameter min.	6 mm
Connection cross section solid mm ² max.	2.5 mm ²
Connection cross section solid mm ² min.	0.2 mm ²
Connection cross section fine stranded mm ² max.	2.5 mm ²
Connection cross section fine stranded mm ² min.	0.2 mm ²
Terminations per pole	1
Connection cross section stranded AWG min.	20 AWG
Connection cross section stranded AWG max.	14 AWG
sheath strip length	30 mm
Wire strip length	8 mm

Model

Model	male
-------	------

Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Fire load	0 kWh
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated
UL classification housing	UL-V2
UL classification strain relief	UL-V2

Dimensions

Length	80 mm
Width	34.6 mm
Height	34.6 mm

Note

Note	Wires with 2,5 mm ² only without ferrules; 3 poles max. 20A, 3 poles max. 5A
------	---

Classification

ECLASS 8.1	27440605
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560

