

## Datasheet

Art.No. 73.300.0353.0

Female insert MIN BUS 3 2,5 40

revos MINI 3 pole + ground, female insert, 400V/10A, screw connection



Art.No.	73.300.0353.0
EAN	4015573229396
Order unit	10 pieces

## Approvals



## Technical data

### General

Model	Female insert
Inflammability class of insulation material acc. with UL94	V2
Colour	Grey
Mating cycles	50
Pollution degree	3
Modular version	No
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

### Connection Data

Connection type	Screw connection
Number of poles	3
Total number of poles (without ground contact)	3
With wire protection	No
Min. conductor diameter rigid (solid/stranded)	0.5 mm <sup>2</sup>
Max. conductor diameter rigid (solid/stranded)	2.5 mm <sup>2</sup>
Protective contact	Yes

### Technical Data UL/CSA

Rated voltage according to UL/CSA	600 V
Rated current according UL	10 A
Rated current according CSA	10 A
Min. conductor cross section flexible wire	0.5 mm <sup>2</sup>

Max. conductor cross section flexible wire	2.5 mm <sup>2</sup>
Conductor cross section flexible AWG wire	22-12 AWG

**Model**

With housing	No
--------------	----

**Contacts**

Contact material	Copper alloy
Surface	Tin-plated
Contact resistance	≤ 2 mOhm
Wire strip length	4 mm

**Screws head design/recomm. Torque**

Mounting screws	M3/0.5-0.7 Nm Slot
Clamping screws	M3/0.5-0.7 Nm Slot
Ground conductor screws	M3/0.5-0.7 Nm Slot


**Technical Data DIN EN 61984**

Nominal voltage	400 V
Rated voltage face/ground	250 V
Nominal current	10 A
Rated impulse voltage	4 kV

**Classification**

ECLASS 8.1	27440205
ETIM 6.0	EC000438
ETIM 5.0	EC000438
ETIM 4.0	EC000438
ETIM 3.0	EC000438

Drawings



4  
1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
M1  
M2  
M3  
L  
G  
i  
11.1  
12.1  
1.1

Nichtergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet.  
The reproduction, distribution and utilization of this document as well as the remanufacture of its contents is others without express authorization is prohibited.