

# OMMO 350W Single Output Switching Power Supply MS-350 series



## ■ Features :

- Universal AC input/Full range
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
- 100% full load burn-in test
- 2 years warranty

## SPECIFICATION




MODEL	MS-350-5	MS-350-12	MS-350-15	MS-350-24
DC VOLTAGE	5V	12V	15V	24V
RATED CURRENT	60A	29A	23.2A	14.6A
CURRENT RANGE	0~60A	0~29A	0~23.2A	0~14.6A
RATED POWER	300W	348W	348W	350.4W
RIPPLE & NOISE(max.) Note 2	80mVp-p	120mVp-p	120mVp-p	150mVp-p
VOLTAGE ADJ. RANGE	4.75~5.5V	10.8~13.2A	13.5~16.5A	21.6~26.4V
VOLTAGE TOLERANCE Note 3	± 2.0%	± 1.0%	± 1.0%	± 1.0%
LINE REGULATION	± 1.0%	± 1.0%	± 1.0%	± 1.0%
LOAD REGULATION	± 1.0%	± 1.0%	± 1.0%	± 1.0%
SETUP,RISE,TIME	1000ms, 30ms/230VAC	100ms,30ms/115VAC (at full load)		
HOLD UP TIME	100ms/230VAC	21ms/115VAC (at full load)		
VOLTAGE RANGE	176~264VAC			
FREQUENCY RANGE	47~63Hz			
EFFICIENCY(Typ.)	80%	82%	84%	86%
AC CURRENT(Typ.)	3.5A/230VAC			
INRUSH CURRENT(Typ.)	COLD START: 15A/115VAC 30A/230VAC			
OVER LOAD	Above 110%~150%rated output power			
PROTECTION	Protection type: Hiccup mode,recovers automatically after fault condition is removed			
OVER VOLTAGE	5.75~6.75V	13.8~16.2V	17.25~20.25V	27.6~32.4V
WORKING TEMP.	Protection type: Hiccup mode,recovers automatically after fault condition is removed			
WORKING HUMIDITY	-10~+60°C (Refer to " Derating Curve" )			
STORAGE TEMP.,HUMIDITY	20~90%RH,non-condensing			
TEMP.COEFFICIENT	~40~+85°C,10~95%RH			
VIBRATION	± 0.03%/°C(0~50°C)			
SAFETY STANDARDS	10~500Hz, 2G 10min/1cycle, period for 60min.X, Y, Zaxes			
WITHSTAND VOLTAGE	Approved UL1012, TUV EN60950 1			
ISOLATION RESISTANCE	I/P-O/P:3KVAC			
EMC EMISSION	IP-O/P.:100M Ohms / 500VDC/ 25°C/ 70% RH			
EMC IMMUNITY	Approved EN55022(CISPR22)Class B,EN61000-3-2,-3			
MTBF	Approved E61000-4-2,3,4,5,EN55024,light industry level,criteria A			
DIMENSION	≥441.5K hrs. MIL-HDBK-217F(25°C)			
PACKING	199*110*50mm(W*H*D)			
	0.8Kg; 20pcs/16Kg/1.02CUFT			
NOTE:	<ol style="list-style-type: none"> <li>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</li> <li>2. Ripple &amp; noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf &amp; 47uf parallel capacitor.</li> <li>3. Tolerance:includes set up tolerance,line regulation and load regulation.</li> </ol>			

# OMMO 350W Single Output Switching Power Supply MS-350 series

## Mechanical Specification

Case No. Wx906 AU:Unit:mm




## Terminal Pin No. Assignment


Pin No.	Assignment	Pin No.	Assignment
1	AC/L	4,5,6	-V
2	AC/N	7,8,9	+V
3	FG		

Fosc: 66KHZ


## Block Diagram



## Derating Curve



## Static Characteristics



Load (%)

OUTPUT VOLTAGE (VDC)

AMBIENT TEMPERATURE (°C)

INPUT VOLTAGE (VAC) 60HZ

Ta=25°C

RIPPLE (mVp-p)