



Potentiometer, Classical, M22, 22.5 mm, R 100 kΩ, P 0.5 W, Bezel: titanium

Part no. M22-R100K
229493
EL Number 4355467
(Norway)

General specifications		
Product name		Eaton Moeller® series M22 Potentiometer
Part no.		M22-R100K
EAN		4015082294939
Product Length/Depth		70 millimetre
Product height		29 millimetre
Product width		29 millimetre
Product weight		0.034 kilogram
Compliances		CE Marked
Certifications		CSA File No.: 012528 EN 60947-5 UL IEC/EN 60947 UL Category Control No.: NKCR CSA Std. C22.2 No. 14-05 VDE 0660 CE CSA Class No.: 3211-03 CSA-C22.2 No. 94-91 IEC/EN 60947-5 CSA-C22.2 No. 14-05 UL File No.: E29184 CSA Std. C22.2 No. 94-91 UL 508 IEC 60947-5 VDE CSA
Product Tradename		M22
Product Type		Potentiometer
Product Sub Type		None
Features & Functions		
Bezel color		Titanium
Design		Classical
Electric connection type		Screw connection
Fitted with:		3 individual screw terminals
General information		
Accuracy		± 10 % (linear), Resistance value
Degree of protection		NEMA Other IP66
Lifespan, mechanical		25,000 Operations
Opening diameter		22.5 mm
Overvoltage category		III
Pollution degree		3
Rated impulse withstand voltage (Uimp)		4000 V AC
Type		Potentiometer
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities		

Terminal capacity (solid)			0.5 - 1.5 mm ²
Terminal capacity (stranded)			0.5 - 1.5 mm ²
Tightening torque			0.5 Nm, Screw terminals
Electrical rating			
Power consumption			0.5 W
Rated insulation voltage (Ui)			250 V
Rated power			0.5 V-A
Resistance			100000 Ohm
Communication			
Connection to SmartWire-DT			No
Design verification			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0.5 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Potentiometer for command devices (EC001027)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Potentiometer for command devices (ecl@ss13-27-37-12-27 [AKF045019])			
Resistance		Ohm	100000
Power consumption		W	0.5
Hole diameter		mm	22.5
Number of revolutions			1 - 1
Type of electric connection			Screw connection
Degree of protection (IP)			IP66
Degree of protection (NEMA)			Other